



TILE GROUT



Grout

Description:

PAVIKRETE TILE GROUT is used in filling tile joints/gaps. It does not allow water to seep into the back of the tile and cause dislocation. It firmly holds the tiles together to provide a hard wearing, non dusting surface to the floor tiles. It is recommended for filling both vertical and horizontal joints of the tile up to 12 mm.

Features & Benefits:

- Easy to use & clean. Polymer modified. Non dusting/abrasion.
- High bonding, compressive and tensile strength ensures care free joints up to the life of the tile.
- Excellent matching of colours of tile. UV resistant. Avoid crack formation with negligible shrinkage.

Application Area:

PAVIKRETE TILE GROUT is basically used to provide smooth waterproof hard wearing tile joints matching environment of tile. It is used in domestic floor and wall tiles and also in other areas like commercial establishment, interiors, exteriors, dry areas, laboratories, bakeries, super markets, show rooms, hospitals, hotels swimming pools & showers etc.

Colour:

Refer to the shade card.

Pack Size:

1 kg pouch & 10 kg bag.

Shelf Life:

12 months shelf life in unopened conditions.

Technical Details:

Parameters	Properties
Joint width	2-12 mm
Pot Life	30 minutes
Curing Time	24 Hours
Mixing Ratio - Water : Grout	1:3
Compressive Strength, kN @ 24 hours	4:00 min